STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING AMENDED REPORT DIVISION OF OIL, GAS AND MINING												
APPLICATION FOR PERMIT TO DRILL								1. WELL NAME and NUMBER Albert 11-22-3-3W				
2. TYPE OF WORK DRILL NEW WELL REENTER P&A WELL DEEPEN WELL DEEPEN WELL								3. FIELD OR WILDCAT WILDCAT				
4. TYPE O	F WELL		Oil Well Coalbe	ed Methane				5. UNIT or COMMUNITIZATION AGREEMENT NAME				
6. NAME	OF OPERATOR		NEWFIELD PRODUC	CTION COM	PANY		7	7. OPERATOR PHONE	435 646-	-4825		
8. ADDRESS OF OPERATOR Rt 3 Box 3630 , Myton, UT, 84052								O. OPERATOR E-MAIL	ozier@ne	wfield.com	n	
	RAL LEASE NUM L, INDIAN, OR S		<u> </u>	11. MINER	RAL OWNERSHIP	A CTATE A FEE		12. SURFACE OWNERS	SHIP DIAN (1811)	CTATE		
13. NAME		4-20-Ĥ62-6189 OWNER (if box 1:	2 = 'fee')	FEDERA	INDIAN (STATE FEE		14. SURFACE OWNER	-	STATE (E (
15. ADDR	ESS OF SURF	ACE OWNER (if bo	x 12 = 'fee')				1	16. SURFACE OWNER	E-MAIL (if box 12	= 'fee')	
17. INDIA	N ALL OTTEF C	OR TRIBE NAME				PRODUCTION FROM	1	19. SLANT				
	2 = 'INDIAN')	Jte Indian Tribe		YES	E FORMATIONS (Submit Commin	gling Application) NO	<u> </u>	VERTICAL DIRI	ECTIONAL	но	ORIZONT	AL 🔵
20. LOC	ATION OF WEL	L	FC	OTAGES	Q	TR-QTR SEC	TION	TOWNSHIP	RAI	NGE	МЕ	RIDIAN
LOCATIO	ON AT SURFAC	E	2170 FS	SL 2318 F\	WL	NESW 2	2	3.0.6	3.0	W		U
Top of U	Jppermost Pro	ducing Zone	2170 FS	SL 2318 F\	WL	NESW 2	2	30 S	3.0	W		U
At Total			2170 FS	SL 2318 F\		NESW 2		3.0 S	3.0			U
21. COUN	NTY	UINTAH				12		23. NUMBER OF ACRE	S IN DRIL	LING UNIT	Г	
				25. DISTA (Applied	NCE TO NEAREST V For Drilling or Com 2	pleted)	2	26. PROPOSED DEPTH MD: 10300 TVD: 10300				
				28. BOND	29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF AP 437478							
		5302			RLB0	0100473		WATER RIGHTS APPRO			PPLICABL	-E
		5302	a	His		0100473 Cement Information	\	WATER RIGHTS APPRO			PPLICABL	-E
String	Hole Size	5302 Casing Size	Length	Ho Weight	Casing, and	Cement Information		WATER RIGHTS APPRO			Yield	Weight
String Cond	Hole Size		Length 0 10		Casing, and	Cement Information ad Max Mud Wt.				78		
		Casing Size		Weight	Grade & Three	Cement Information ad Max Mud Wt.		Cement Class G mium Lite High Stre	4374	Sacks 35 51	Yield 1.17 3.53	Weight 15.8 11.0
Cond	17.5 12.25	Casing Size	0 10 0	Weight 37.0 36.0	Grade & Three H-40 ST&C J-55 ST&C	Cement Information ad Max Mud Wt. 0.0 8.3		Cement Class G mium Lite High Stre Class G	4374	Sacks 35 51 154	Yield 1.17 3.53 1.17	Weight 15.8 11.0 15.8
Cond	17.5	Casing Size	0 - 0	Weight 37.0	Grade & Three	Cement Information ad Max Mud Wt. 0.0 8.3		Cement Class G mium Lite High Stre Class G 35/65 Poz	4374	Sacks 35 51 154 254	Yield 1.17 3.53 1.17 3.53	Weight 15.8 11.0 15.8 11.0
Cond	17.5 12.25	Casing Size	0 10 0	Weight 37.0 36.0	Grade & Three H-40 ST&C J-55 ST&C	Cement Information ad Max Mud Wt. 0.0 8.3 9.5		Cement Class G mium Lite High Stre Class G	4374	Sacks 35 51 154	Yield 1.17 3.53 1.17	Weight 15.8 11.0 15.8
Cond Surf	17.5 12.25 8.75	Casing Size 14 9.625	0 100	37.0 36.0 26.0	Casing, and Grade & Three H-40 ST&C J-55 ST&C P-110 LT&C	Cement Information ad Max Mud Wt. 0.0 8.3 9.5		Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz	4374	Sacks 35 51 154 254 255	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf	17.5 12.25 8.75 6.125	Casing Size 14 9.625 4.5	0 10 0 0 10 0 0 - 8085 7885 - 10300	37.0 36.0 26.0	P-110 LT&C	Cement Information Max Mud Wt. 0.0 8.3	Pre	Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz	4374	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf	17.5 12.25 8.75 6.125	Casing Size 14 9.625 4.5	0 10 0 0 10 0 0 - 8085 7885 - 10300	37.0 36.0 26.0 11.6	P-110 LT&C	Cement Information ad Max Mud Wt. 0.0 8.3 9.5 11.5	Pre	Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz	4374	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf	17.5 12.25 8.75 6.125	Casing Size 14 9.625 4.5 RIFY THE FOLL	0 10 0 0 - 8085 7885 - 10300	37.0 36.0 26.0 11.6	P-110 LT&C ACCORDANCE W	Cement Information ad Max Mud Wt. 0.0 8.3 9.5 11.5 HMENTS TH THE UTAH OIL A	Pre ND GAS (Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz	ength	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf	17.5 12.25 8.75 6.125	Casing Size 14 9.625 4.5 ATUS OF SURFACE	0 10 0 0 - 8085 7885 - 10300 DWING ARE ATTAC	37.0 36.0 26.0 11.6 CHED IN A	P-110 LT&C ACCORDANCE W NEER	Cement Information ad Max Mud Wt. 0.0 8.3 9.5 11.5 HMENTS TH THE UTAH OIL A	ND GAS (Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz	ength	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf I1 Prod AP	17.5 12.25 8.75 6.125	Casing Size 14 9.625 4.5 ATUS OF SURFACE	0 10 0 0 - 8085 7885 - 10300 DWING ARE ATTAC	37.0 36.0 26.0 11.6 CHED IN A	P-110 LT&C ACCORDANCE W NEER	Cement Information and Max Mud Wt. 0.0 8.3 9.5 11.5 HMENTS TH THE UTAH OIL A COMPLETE DR FORM 5. IF OPE	ND GAS (Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz	ength ENERAL ASE OWN	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf I1 Prod AP	17.5 12.25 8.75 6.125 VEIL PLAT OR METABORITY OF ST	Casing Size 14 9.625 4.5 ATUS OF SURFACE	0 10 0 0 - 8085 7885 - 10300 DWING ARE ATTAC	Weight 37.0 36.0 26.0 11.6 CHED IN A R OR ENGI T (IF FEE S	P-110 LT&C ACCORDANCE W NEER SURFACE)	Cement Information and Max Mud Wt. 0.0 8.3 9.5 11.5 HMENTS TH THE UTAH OIL A COMPLETE DR FORM 5. IF OPE	ND GAS (Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz	ength ENERAL ASE OWN	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0
Cond Surf I1 Prod AF NAME D SIGNATU	17.5 12.25 8.75 6.125 VEIL PLAT OR METABORITY OF ST	Casing Size 14 9.625 4.5 RIFY THE FOLL MAP PREPARED BY ATUS OF SURFACE JRVEY PLAN (IF D	0 10 0 0 - 8085 7885 - 10300 DWING ARE ATTAC	T (IF FEE S	P-110 LT&C ACCORDANCE W NEER BURFACE) LLY DRILLED) TILE Permitting Age	Cement Information and Max Mud Wt. 0.0 8.3 9.5 11.5 HMENTS TH THE UTAH OIL A COMPLETE DR FORM 5. IF OPE	ND GAS (Cement Class G mium Lite High Stre Class G 35/65 Poz 50/50 Poz 50/50 Poz CONSERVATION GE AN OTHER THAN THE LEA	ength ENERAL ASE OWN	Sacks 35 51 154 254 255 113	Yield 1.17 3.53 1.17 3.53 1.29	Weight 15.8 11.0 15.8 11.0 14.0

API Well Number: 43047532720000

Newfield Production Company 11-22-3-3W NE/SW Section 22, T3S, R3W Duchesne County, UT

Drilling Program

1. Formation Tops

Uinta surface
Green River 3,460'
Garden Gulch member 6,185'
Wasatch 8,690'
TD 10,300'

2. Depth to Oil, Gas, Water, or Minerals

Base of moderately saline 530' (water)

Green River 6,185' - 8,690' (oil)

Wasatch 8,690' - TD (vil)

3. Pressure Control

Section BOP Description

Surface 12-1/4" diverter

Interm/Prod

The BOP and related equipment shall meet the minimum requirements of Onshore
Oil and Gas Order No. 2 for equipment and testing requirements, procedures, etc

for a 5M system.

A 5M BOP system will consist of 2 ram preventers (double or two singles) and an annular preventer (see attached diagram). A choke manifold rated to at least 5,000 psi will be used.

4. Casing

Description	Interval		Weight	G 1.	G.	Pore	MW @	Frac	Safety Factors		
Description	Тор	Bottom	(ppf)	Grade	Coup	Press @ Shoe	Shoe	Grad @ Shoe	Burst	Collapse	Tension
Conductor	0'	60'	37	H-40	Weld						
14	U	00									
Surface	0' 1,000	1 000'	36	J-55	STC	8.33	8.33	12	3,520	2,020	394,000
9 5/8		1,000	30						6.27	6.35	10.94
Intermediate	0' 8.	8,085'	26	P-110	LTC	9	9.5	15	9,960	6,210	693,000
7	U								2.61	1.95	3.30
Production	7 0051	10 200!	11.6	D 110	I TO		11.5		10,690	7,560	279,000
4 1/2	7,885'	10,300'	11.6	P-110	LTC	11	11.5		2.20	1.47	2.34

Assumptions:

Surface casing MASP = (frac gradient + 1.0 ppg) - (gas gradient)

Intermediate casing MASP = (reservoir pressure) - (gas gradient)

Production casing MASP = (reservoir pressure) - (gas gradient)

All colleges calculations assume fully executed assing with a gas gradient

All collapse calculations assume fully evacuated casing with a gas gradient

All tension calculations assume air weight of casing

Gas gradient = 0.1 psi/ft

All casing shall be new.

All casing strings shall have a minimum of 1 centralizer on each of the bottom 3 joints.

5. Cement

Job	Hole Size	Fill	Slurry Description	ft ³	OH excess	Weight (ppg)	Yield (ft³/sk)
Conductor	17 1/2	60'	Class G w/ 2% KCl + 0.25 lbs/sk Cello Flake	35	15%	15.8	1.17
Surface Lead	12 1/4	500'	Premium Lite II w/ 3% KCl + 10% bentonite	180 51	15%	11.0	3 53
Surface Tail	12 1/4	500'	Class G w/ 2% KCl + 0.25 lbs/sk-Cello Flake	180 154	15%	15.8	1.17
Intermediate Lead	8 3/4	5,185'	65% Class G / 35% Poz + 10% Bentonite	896 254	15%	11.0	3.53
Intermediate Tail	8 3/4	1,900'	50/50 Poz / Class G + (% Bens hite	329 255	15%	14.0	1.29
Production Tail	6 1/8	2,415'	50/50 Poz Class G was 1% bentonite	262 113	15%	14.0	2.31

The surface casing will be cemented to surface. In the event that cement does not reach surface during the primary cement job, a remedial job will be performed.

Actual center volumes for the intermediate and production casing strings will be calculated from up open to e caliper log, plus 15% excess.

6. Type and Characteristics of Proposed Circulating Medium

<u>Interval</u> <u>Description</u>

Surface - 1,000'

An air and/or fresh water system will be utilized. If an air rig is used, the blooie line discharge may be less than 100' from the wellbore in order to minimize location size. The blooie line is not equipped with an automatic igniter. The air compressor may be located less than 100' from the well bore due to the low possibility of combustion with the air/dust mixture. Water will be on location to be used as kill fluid, if necessary.

1,000' - TD A water based mud system will be utilized. Hole stability may be improved with additions of KCl or a similar inhibitive substance. In order to control formation pressure the system will be weighted with additions of bentonite, and if conditions warrant, with barite.

API Well Number: 43047532720000

Anticipated maximum mud weight is 11.5 ppg.

7. Logging, Coring, and Testing

Logging: A dual induction, gamma ray, and caliper log will be run from TD to the base of the

surface casing. A compensated neutron/formation density log will be run from TD to the top of the Garden Gulch formation. A cement bond log will be run from PBTD to the

cement top behind the production casing.

Cores: As deemed necessary.

DST: There are no DST's planned for this well.


8. Anticipated Abnormal Pressure or Temperature


Maximum anticipated bottomhole pressure will be approximately equal to total depth (feet) multiplied by a 0.57 psi/ft gradient.

No abnormal temperature is expected. No H₂S is expected.

9. Other Aspects

This is planned as a vertical well.






Duchesne County, UT.

TOPOGRAPHIC MAP







P: (435) 781-2501 F: (435) 781-2518 N

180 NORTH VERNAL AVE. VERNAL, UTAH 84078


DRAWN BY:	D.C.R.	REVISED:	VERSION:
DATE:	04-12-2012	2.7	V1
SCALE:	1"=2,000'		V1

NEWFIELD EXPLORATION COMPANY

11-22-3-3W SEC. 22, T3S, R3W, U.S.B.&M. **Duchesne County, UT.**

TOPOGRAPHIC MAP







P: (435) 781-2501 F: (435) 781-2518 N

180 NORTH VERNAL AVE. VERNAL, UTAH 84078


DRAWN BY:	D.C.R.	REVISED:	VERSION:
DATE:	04-12-2012		V1
SCALE:	1"= 2,000'		VI

NEWFIELD EXPLORATION COMPANY

11-22-3-3W SEC. 22, T3S, R3W, U.S.B.&M. **Duchesne County, UT.**

TOPOGRAPHIC MAP

SHEET C





180 NORTH VERNAL AVE. VERNAL, UTAH 84078


DRAWN BY:	D.C.R.	REVISED:	VERSION:
DATE:	04-12-2012		V1
SCALE:	1 " = 2,000 '		VI

11-22-3-3W SEC. 22, T3S, R3W, U.S.B.&M. **Duchesne County, UT.**


TOPOGRAPHIC MAP





Typical 5M BOP stack configuration





Typical 5M choke manifold configuration












WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 10/1/2012 API NO. ASSIGNED: 43047532720000 WELL NAME: Albert 11-22-3-3W **OPERATOR:** NEWFIELD PRODUCTION COMPANY (N2695) PHONE NUMBER: 435 719-2018 **CONTACT:** Don Hamilton PROPOSED LOCATION: NESW 22 030S 030W Permit Tech Review: SURFACE: 2170 FSL 2318 FWL **Engineering Review:** BOTTOM: 2170 FSL 2318 FWL Geology Review: **COUNTY: UINTAH** LONGITUDE: **LATITUDE: 40.20599** UTM SURF EASTINGS: 567218.00 FIELD NAME: WILDCAT LEASE TYPE: 2 - Indian PROPOSED PRODUCING FORMATIO (S): GREEN RIVER-WASATCH LEASE NUMBER: 14-20-H62-6189 OALBED METHANE: NO SURFACE OWNER: 2 - Indian **RECEIVED AND/OR REVIEWED:** ✓ PLAT R649-2-3. Bond: INDIAN - RLB00100473 Unit: **Potash** R649-3-2. General Oil Shale 190-5 Oil Shale 1 R649-3-3. Exception Oil Shale 90-13 **Drilling Unit** Water Permit: 437478 Board Cause No: Cause 139-90 Effective Date: 5/9/2012 **RDCC Review:** Siting: Suspends General Siting Fee Surface Agreement Intent to Commingle R649-3-11. Directional Drill **Commingling Approved** Presite Completed

Comments:

Stipulations: 4 - Federal Approval - dmason



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA

Division Director

November 08, 2012

NEWFIELD PRODUCTION COMPANY Rt 3 Box 3630 Myton, UT 84052

Re: Application for Permit to Drill - UINTAH County, Utah

Ladies and Gentlemen:

The Application for Permit to Drill (APD) for the Albert 11-22-3-3W well, API 43047532720000 that was submitted October 01, 2012 is being returned unapproved. If you plan on drilling this well in the future, you must first submit a new application.

Should you have any questions regarding this matter, please call me at (801) 538-5312.

Sincerely,

Diana Mason Environmental Scientist

Enclosure

cc: Bureau of Land Management, Vernal, Utah

